

PAINTMASTER (2000) LIMITED

HEAD OFFICE:-

**UNITS 12 – 17, BINGSWOOD INDUSTRIAL ESTATE,
WHALEY BRIDGE, HIGH PEAK, DERBYSHIRE, SK23 7LY**

TELEPHONE: 01663-733633 FAX: 01663-735366

DATA SHEET

FACTORY EMULSION EMULSION

DESCRIPTION

A full-bodied, high opacity matt finish emulsion. Manufactured from lead-free pigments finely dispersed in a P.V.A copolymer resin. Air drying water-borne.

USES

Ideal for interior use

SPECIAL PROPERTIES

High opacity and easy to apply. Allows thick coat application by airless spray. Semi-porous structure allows new plaster to breathe and dry out.

SPREADING RATE

Approximately 12-14 sq./metres per Litre, depending on surface porosity and texture.

DRYING TIME

Under normal conditions, approximately 2 hours.

APPLICATION

Brush, roller, conventional and airless spray. Stir well before use. On porous surfaces, the first coat may be thinned with up to 10% by volume of clean water to ease application. Do not over thin, or opacity and application properties suffer. Two coats, allowing 2 hours between coats, are recommended. For spray application, thin with clean water as required. Do not apply when air of surface temperature is below 5 degrees C. High humidity can prolong drying time.

EQUIPMENT CLEANER

Warm water.

STORAGE PRECAUTIONS

Protect from frost and secure lid on firmly to prevent paint from drying out.

SURFACE PREPARATION

Ensure that bare plaster surfaces to be painted are dry, clean and free from dust

AVAILABLE IN 20 LTS AND 205 LTR BARRELS