

PAINTMASTER (2000) LIMITED

HEAD OFFICE:-

**UNITS 12 – 17, BINGSWOOD INDUSTRIAL ESTATE,
WHALEY BRIDGE, HIGH PEAK, DERBYSHIRE, SK23 7LY**

TELEPHONE: 01663-733633 FAX: 01663-735366

DATA SHEET

SMOOTH OR TEXTURED MASONRY PAINT

DESCRIPTION

This product is specially formulated to give a durable and colourfast protection to exterior masonry and rendering, including concrete, roughcast, pebbledash and brickwork. Based on an Acrylic resin, it is easier to apply; with less spatter and mess, while helping to bridge hairline cracks. It contains an algacide and fungicide to inhibit mould growth and helps it stay cleaner longer.

BEFORE USE

Ensure all surfaces to be painted are sound, clean and dry. Remove any loose or flaking paint and areas affected by mould; lichen, algae or moss should be treated with a suitable fungicidal wash. Fill any small holes and if surface is powdery, seal with a stabilizing primer

SPREADING RATE

Approx 6-8 sq meters per litre depending on surface porosity and texture.

DRYING TIME

Under normal conditions 2-4 hours

APPLICATION

Brush or Roller. Thinning is only necessary when sealing new or bare surfaces, in which case add up to one part water to five parts paint.

EQUIPMENT CLEANER

Warm water

STORAGE

Protect from frost and secure lid firmly to prevent paint from drying out.

AVAILABLE IN 20 LTS AND 205 LTR BARRELS