

PAINTMASTER (2000) LIMITED

HEAD OFFICE:-

**UNITS 12 – 17, BINGSWOOD INDUSTRIAL ESTATE,
WHALEY BRIDGE, HIGH PEAK, DERBYSHIRE, SK23 7LY**

TELEPHONE: 01663-733633 FAX: 01663-735366

DATA SHEET

POLYURETHANE FLOOR PAINT

DESCRIPTION

Air-drying, solvent borne, based on a Polyurethane resin, provides a tough durable Floor Paint. General purpose one pack Floor Paint. Available in Clear, Red Oxide, Green, Mid Grey, and Light Grey.

USES

Suitable for use on concrete, metal and wooden floors, in factories, garages, workshops etc. **NOT SUITABLE FOR ASPHALT FLOORS OR POWER FLOATED CONCRETE FLOORS.**

SPECIAL PROPERTIES

Dries to a semi-gloss finish and is very hard wearing. It is easily cleaned and will withstand regular washing. It is resistant to most oils.

SPREADING RATE

Approximately 6-8 sq./metres per Litre, depending on surface porosity and texture.

DRYING TIME

Under normal conditions it is touch dry in approximately 6 hours, second coat can be painted after 24 hours.

APPLICATION

Brush, Roller, or Airless Spray.

STORAGE PRECAUTIONS

Store away from heat and naked flames. Secure lid between uses to prevent paint hardening.

SURFACE PREPARATION

Ensure all floor surfaces to be painted are clean, dry and free from oil and grease. It is always recommended to allow new concrete floors to mature for several months prior to painting. New floors should also be sealed prior to painting topcoat.

THINNERS

White Spirit or Turpentine Substitute can be used for thinning.

AVAILABLE IN 20 LTS AND 205 LTR BARRELS