

PAINTMASTER (2000) LIMITED

HEAD OFFICE:-

**UNITS 12 – 17, BINGSWOOD INDUSTRIAL ESTATE,
WHALEY BRIDGE, HIGH PEAK, DERBYSHIRE, SK23 7LY**

TELEPHONE: 01663-733633 FAX: 01663-735366

DATA SHEET

OXIDE GLOSS PAINT

DESCRIPTION

Air-drying, solvent borne, based on a White Spirit resin, provides a tough durable gloss finish. General purpose Gloss Paint. Available in Grey, Red, and Green.

USES

Suitable for use on metal and wood.

SPECIAL PROPERTIES

Dries to a gloss finish and is very hard wearing. It is easily cleaned and will withstand regular washing.

SPREADING RATE

Approximately 6-8 sq./metres per Litre, depending on surface porosity and texture.

DRYING TIME

Under normal conditions it is touch dry in approximately 6 hours, second coat can be painted after 24 hours.

APPLICATION

Brush or Roller.

STORAGE PRECAUTIONS

Store away from heat and naked flames. Secure lid between uses to prevent paint hardening.

SURFACE PREPARATION

Ensure all surfaces to be painted are clean, dry and free from oil and grease.

THINNERS

White Spirit or Turpentine Substitute can be used for thinning.

AVAILABLE IN 20 LTS AND 205 LTR BARRELS