

# **PAINTMASTER (2000) LIMITED**

## **HEAD OFFICE:-**

**UNITS 12 – 17, BINGSWOOD INDUSTRIAL ESTATE,  
WHALEY BRIDGE, HIGH PEAK, DERBYSHIRE, SK23 7LY**

**TELEPHONE: 01663-733633      FAX: 01663-735366**

## **DATA SHEET**

### **POLYURETHANE VARNISH**

#### **DESCRIPTION**

Air-drying, solvent borne, based on a Polyurethane resin, provides a tough durable Gloss or Satin finish. General purpose one pack Varnish. Available in clear only.

#### **USES**

Suitable for use on concrete, metal, and wood.

#### **SPECIAL PROPERTIES**

Dries to either a matt, gloss or semi-gloss finish and is very hard wearing. It is easily cleaned and will withstand regular washing. It is resistant to most oils.

#### **SPREADING RATE**

Approximately 6-8 sq./metres per Litre, depending on surface porosity and texture.

#### **DRYING TIME**

Under normal conditions it is touch dry in approximately 6 hours, second coat can be painted after 24 hours.

#### **APPLICATION**

Brush or Roller.

#### **STORAGE PRECAUTIONS**

Store away from heat and naked flames. Secure lid between uses to prevent paint hardening.

#### **SURFACE PREPARATION**

Ensure all surfaces to be painted are clean, dry and free from oil and grease.

#### **THINNERS**

White Spirit or Turpentine Substitute can be used for thinning.

**AVAILABLE IN 20 LTS AND 205 LTR BARRELS**