

Data Sheet

Paintmaster Chlorinated Rubber/Acrylated Parlour Paint

1. Identification of the substance/preparation and of the company/undertaking

PRODUCT NAME	Paintmaster Chlorinated Rubber/ Acrylated Parlour Paint
PRODUCT INFO	Solvent based paint, suitable for interior and exterior use on new or previously painted steelwork and masonry, where conditions are prone to high levels of moisture/heavy condensation paint will provide excellent resistance. Can withstand frequent washing down, which makes it ideal for use in dairies etc. It is also resistant to splashing with alcohols, concentrated acid and alkalis.
COLOURS AVAILABLE	All Colours available. British Standard Colours or RAL Colours.
SUPPLIER	Paintmaster
COVERAGE	Approximately 8 square metres per litre.
APPLICATION	Brush, Roller, Spray
DRYING TIME	Under normal circumstances it should be touch dry in 6-8hrs if well ventilated and conditions are dry.
STORAGE	Store away from naked flames. Secure lid on firmly between uses to prevent paint from skinning.
SURFACE PREP	Apply to a clean dry surface. Ensure any rust or damp is removed prior to application.
THINNERS	White Spirit can be used for thinning.

AVAILABLE IN 20 LTS AND 205 LTR BARRELS

Safety Precautions

Refer to MSDS before use. Safety precautions must be strictly followed during storage, handling and use.