

For MSDS & Technical Assistance ~ Email: Sales@paintmaster.co.uk

Data Sheet

Paintmaster Acrylic Industrial and Agricultural Barn & Shed

1. Identification of the substance/preparation and of the company/undertaking

PRODUCT NAME	Paintmaster Acrylic Industrial and Agricultural Barn & Shed
PRODUCT INFO	Hard wearing, durable exterior acrylic paint suitable for Industrial and Agricultural buildings.
COLOURS AVAILABLE	Grey, Red, Green, Black as well as British Standard Colours or RAL Colours.
SUPPLIER	Paintmaster
COVERAGE	Approximately 6-8 sq metres per litre.
APPLICATION	Brush, roller or spray.
DRYING TIME	Under normal circumstances the product should be touch dry within 4-6hrs if well ventilated and conditions are dry. Re-coat possible after 24hrs. Please note that drying times can differ in cold and damp conditions. Applying the product in thin coats will allow a faster drying time and better finish.
STORAGE	Protect from frost and secure lid firmly to prevent paint from drying out.
SURFACE PREP	Ensure all surfaces are sound and clean, free from algae and moss. Remove any loose or flaking paint.
THINNERS	Can be let down with water if needed.

AVAILABLE IN 20 LTS AND 205 LTR BARRELS

Safety Precautions

Refer to MSDS before use. Safety precautions must be strictly followed during storage, handling and use.