

Data Sheet

Paintmaster Acrylic Smooth Masonry

1. **Identification of the substance/preparation and of the company/undertaking**

PRODUCT NAME	Paintmaster Acrylic Smooth Masonry
PRODUCT INFO	An exterior quality water based emulsion paint based on an all acrylic resin. It contains a fungicide to inhibit mould growth on the paint film which helps it stay cleaner for longer. It is particularly suitable for use in changeable weather.
COLOURS AVAILABLE	White & Magnolia as well as British Standard Colours or RAL Colours.
SUPPLIER	Paintmaster
COVERAGE	Approximately 6-8 sq metres per litre.
APPLICATION	Brush, roller or spray.
DRYING TIME	Under normal conditions 2 – 4hrs
STORAGE	Protect from frost and secure lid firmly to prevent paint from drying out.
SURFACE PREP	Ensure all surfaces are sound and clean, free from algae and moss. Remove any loose or flaking paint.
THINNERS	Can be let down with water if needed.

AVAILABLE IN 20 LTS AND 205 LTR BARRELS

Safety Precautions

Refer to MSDS before use. Safety precautions must be strictly followed during storage, handling and use.