

## Data Sheet

### Paintmaster Acrylic Undercoat

1. **Identification of the substance/preparation and of the company/undertaking**

<b>PRODUCT NAME</b>	Paintmaster Acrylic Undercoat
<b>PRODUCT INFO</b>	Hard wearing, durable acrylic Undercoat.
<b>COLOURS AVAILABLE</b>	White & Magnolia as well as British Standard Colours or RAL Colours.
<b>SUPPLIER</b>	Paintmaster
<b>COVERAGE</b>	Approximately 6-8 sq metres per litre.
<b>APPLICATION</b>	Brush, roller or spray.
<b>DRYING TIME</b>	Under normal circumstances the product should be touch dry within 4-6hrs if well ventilated and conditions are dry. Re-coat possible after 24hrs. Please note that drying times can differ in cold and damp conditions. Applying the product in thin coats will allow a faster drying time and better finish.
<b>STORAGE</b>	Protect from frost and secure lid firmly to prevent paint from drying out.
<b>SURFACE PREP</b>	Ensure all surfaces are sound and clean, free from algae and moss. Remove any loose or flaking paint.
<b>THINNERS</b>	Can be let down with water if needed.

**AVAILABLE IN 20 LTS AND 205 LTR BARRELS**

#### **Safety Precautions**

Refer to MSDS before use. Safety precautions must be strictly followed during storage, handling and use.