

For MSDS & Technical Assistance ~ Email: [Sales@paintmaster.co.uk](mailto:Sales@paintmaster.co.uk)

## Data Sheet

### Acrylic Wood Stain

#### 1. Identification of the substance/preparation and of the company/undertaking

<b>PRODUCT NAME</b>	Acrylic Wood Stain
<b>PRODUCT INFO</b>	Paintmaster Wood Stain offers a rich semi-transparent colour with a tough durable finish. It is water repellent to help prevent wood cracking and splitting. It is also suitable for use on other garden wood and is safe with plants and pets when dry.
<b>COLOURS AVAILABLE</b>	Clear & All Standard Wood Colours
<b>SUPPLIER</b>	Paintmaster
<b>COVERAGE</b>	Approximately 8 square metres per litre.
<b>APPLICATION</b>	Brush, Roller, Spray
<b>DRYING TIME</b>	Under normal circumstances it should be touch dry in 2-4hrs.
<b>STORAGE</b>	Protect from Frost
<b>SURFACE PREP</b>	All surfaces to be treated should be clean, dry and free from loose and flaking material. Treat mould growth with fungicidal wash.
<b>THINNERS</b>	Water can be used for thinning.

#### **AVAILABLE IN 20 LTS AND 205 LTR BARRELS**

#### **Safety Precautions**

Refer to MSDS before use. Safety precautions must be strictly followed during storage, handling and use.