

Data Sheet

Paintmaster Black Bitumen

1. Identification of the substance/preparation and of the company/undertaking

PRODUCT NAME	Paintmaster Black Bitumen
PRODUCT INFO	Solvent based, full bodies black bitumen coating. When dry, the product forms and odourless and taint free bitumen film suitable for the protection of metals, concrete roofing, felt, fibre, cement, corrugated iron, asphalt and wood against water attack. Suitable for use with portable drinking water tank, provides an effective waterproof, weather proof, corrosion resistant protective coating. It is resistant to low concentrations of alkalis and acids and can withstand prolonged oxidation.
COLOURS AVAILABLE	Black
SUPPLIER	Paintmaster
COVERAGE	Approximately 10 square metres per litre. Less on porous surfaces.
APPLICATION	Apply using brush, roller or spray.
DRYING TIME	Under normal circumstances it should be touch dry in 6-8hrs if well ventilated and conditions are dry. Leave 48 hours between coats
STORAGE	Store away from naked flames. Secure lid on firmly between uses.
SURFACE PREP	All surfaces should be degreased, clean and free from dirt. Note: Bitumen may bleed through any paint subsequently applied over it.
THINNERS	White spirit can be used for thinning.

AVAILABLE IN 20 LTS AND 205 LTR BARRELS

Safety Precautions

Refer to MSDS before use. Safety precautions must be strictly followed during storage, handling and use.