

For MSDS & Technical Assistance ~ Email: Sales@paintmaster.co.uk

Data Sheet

Paintmaster Cladding Paint

1. Identification of the substance/preparation and of the company/undertaking

PRODUCT NAME	Paintmaster Cladding Paint
PRODUCT INFO	Hard wearing, water resistant, durable oil based enamel gloss for Cladding.
COLOURS AVAILABLE	All Colours available. British Standard Colours or RAL Colours.
SUPPLIER	Paintmaster
COVERAGE	Approximately 8 square metres per litre.
APPLICATION	Brush, Roller, Spray
DRYING TIME	Under normal circumstances it should be touch dry in 6-8hrs if well ventilated and conditions are dry.
STORAGE	Store away from naked flames. Secure lid on firmly between uses to prevent paint from skinning.
SURFACE PREP	Apply to a clean dry surface. Ensure any rust or damp is removed prior to application.
THINNERS	White Spirit can be used for thinning.

AVAILABLE IN 20 LTS AND 205 LTR BARRELS

Safety Precautions

Refer to MSDS before use. Safety precautions must be strictly followed during storage, handling and use.