

## Data Sheet

### Paintmaster Creocote

#### 1. Identification of the substance/preparation and of the company/undertaking

<b>PRODUCT NAME</b>	Paintmaster Creocote
<b>PRODUCT INFO</b>	An oil-based wood treatment, effective when applied to exterior timbers such as garden sheds, fences and trellis work. The oil based properties provides excellent surface water repellence, restricts weather damage and improves grain definition.
<b>COLOURS AVAILABLE</b>	Dark Brown
<b>SUPPLIER</b>	Paintmaster
<b>COVERAGE</b>	Approximately 8 square metres per litre.
<b>APPLICATION</b>	Apply liberally using brush, roller or spray.
<b>DRYING TIME</b>	Under normal circumstances the product should be touch dry within 6-8hrs if well ventilated and conditions are dry. Re-coat possible after 24 - 48hrs. Please note that drying times can different in cold and damp conditions. Applying the product in thin coats will allow a faster drying time and better finish.
<b>STORAGE</b>	Store away from naked flames. Secure lid on firmly between uses.
<b>SURFACE PREP</b>	Ensure timber is sound, dry and free from dirt. Sealed or painted timbers should be brought back to bare wood. Children and pets should be kept away until dry.
<b>THINNERS</b>	White spirit can be used for thinning.

#### **AVAILABLE IN 20 LTS AND 205 LTR BARRELS**

#### **Safety Precautions**

Refer to MSDS before use. Safety precautions must be strictly followed during storage, handling and use.