

## Sheet

# Paintmaster Drivemaster

### **1. Identification of the substance/preparation and of the company/undertaking**

|                          |   |
|--------------------------|---|
| <b>PRODUCT NAME</b>      | Paintmaster Drivemaster   |
| <b>PRODUCT INFO</b>      | Drivemaster is a superb and easy to apply "Tarmac restorer" designed to rejuvenate and transforms tired tarmac.<br>Drivemaster is a durable and hardwearing tarmac paint and offers a cost effective alternative to replacement of driveway.  |
| <b>COLOURS AVAILABLE</b> | Black & Red   |
| <b>SUPPLIER</b>          | Paintmaster   |
| <b>COVERAGE</b>          | Approximately 6-8 sq metres per litre.  |
| <b>APPLICATION</b>       | Brush, roller or spray.   |
| <b>DRYING TIME</b>       | Under normal circumstances the product should be touch dry within 6-8hrs if well ventilated and conditions are dry.<br>Re-coat possible after 24 - 48hrs.<br>Please note that drying times can different in cold and damp conditions. Applying the product in thin coats will allow a faster drying time and better finish. |
| <b>STORAGE</b>           | Protect from Frost  |
| <b>SURFACE PREP</b>      | Apply to clean dry surfaces. This is not a non slip product.<br>Please add builders sand or silver sand to the product before application if desired.   |
| <b>THINNERS</b>          | Water can be used for thinning.   |

### **AVAILABLE IN 20 LTS AND 205 LTR BARRELS**

#### **Safety Precautions**

Refer to MSDS before use. Safety precautions must be strictly followed during storage, handling and use.