

## Data Sheet

### Paintmaster Line Marking Paint

#### 1. Identification of the substance/preparation and of the company/undertaking

<b>PRODUCT NAME</b>	Paintmaster Line Marking Paint
<b>PRODUCT INFO</b>	A general purpose oil based product for use in factories, workshops etc.  <b>Caution: Not suitable for asphalt.</b>
<b>COLOURS AVAILABLE</b>	Yellow & White
<b>SUPPLIER</b>	Paintmaster
<b>COVERAGE</b>	Approximately 6-8 sq metres per litre.
<b>APPLICATION</b>	Brush or roller
<b>DRYING TIME</b>	Under normal circumstances it should be touch dry in 2-4hrs. Do not use in cold damp conditions.
<b>STORAGE</b>	Store away from naked flames. Secure lid on firmly between uses to prevent paint from skinning.
<b>SURFACE PREP</b>	Apply to clean dry surfaces. Ensure any oil or grease is removed. If new concrete allow to mature for several months and seal prior to applying top coat.
<b>THINNERS</b>	White Spirit can be used for thinning.

#### AVAILABLE IN 20 LTS AND 205 LTR BARRELS

#### **Safety Precautions**

Refer to MSDS before use. Safety precautions must be strictly followed during storage, handling and use.