

For MSDS & Technical Assistance ~ Email: Sales@paintmaster.co.uk

Data Sheet

Oil Based Timber Preserve

1. **Identification of the substance/preparation and of the company/undertaking**

PRODUCT NAME	Oil Based Timber Preserve
PRODUCT INFO	Paintmaster Timber preserve is a colour less general-purpose oil based preserver for interior or exterior use. Suitable for use on fences, sheds, gates and rough sawn surfaces.
COLOURS AVAILABLE	Clear & All Standard Wood Colours
SUPPLIER	Paintmaster
COVERAGE	Approximately 8 square metres per litre.
APPLICATION	Brush, Roller, Spray
DRYING TIME	Under normal circumstances it should be touch dry in 2-4hrs.
STORAGE	Keep in a cool dry place.
SURFACE PREP	All surfaces to be treated should be clean, dry and free from loose and flaking material. Treat mould growth with fungicidal wash.
THINNERS	White Spirit can be used for thinning.

AVAILABLE IN 20 LTS AND 205 LTR BARRELS

Safety Precautions

Refer to MSDS before use. Safety precautions must be strictly followed during storage, handling and use.