

## Data Sheet

# Paintmaster Polyurethane Floor Paint

### 1. Identification of the substance/preparation and of the company/undertaking

<b>PRODUCT NAME</b>	Paintmaster Polyurethane Floor Paint
<b>PRODUCT INFO</b>	<p>Hard wearing, durable polyurethane floor paint designed to protect, seal and colour concrete, wood and stone internal floors. It provides a tough petrol and oil resistant finish with excellent durability. Ideal for factory, garage and workshop floors.</p> <p><b>Caution: Not suitable for asphalt or power floated floors</b></p>
<b>COLOURS AVAILABLE</b>	Red, Lt Grey, Grey and Green
<b>SUPPLIER</b>	Paintmaster
<b>COVERAGE</b>	Approximately 6-8 sq metres per litre.
<b>APPLICATION</b>	Brush, roller or spray.
<b>DRYING TIME</b>	Under normal circumstances it should be touch dry in 6-8 hrs completely dry in 24hrs if well ventilated and conditions are dry.
<b>STORAGE</b>	Store away from naked flames. Secure lid on firmly between uses to prevent paint from skinning.
<b>SURFACE PREP</b>	Apply to clean dry surfaces. Ensure any oil or grease is removed. If new concrete allow to mature for several months and seal prior to applying top coat.
<b>THINNERS</b>	White Spirit can be used for thinning.

### AVAILABLE IN 20 LTS AND 205 LTR BARRELS

#### Safety Precautions

Refer to MSDS before use. Safety precautions must be strictly followed during storage, handling and use.

