

Data Sheet

Paintmaster Polyurethane Floor Sealer

1. Identification of the substance/preparation and of the company/undertaking

PRODUCT NAME	Paintmaster Polyurethane Floor Sealer
PRODUCT INFO	<p>A polyurethane based sealer provides a base coat prior to topcoat being applied. Specifically formulated to seal new concrete. Recommended for factories, garages, workshops etc.</p> <p>Caution: Not suitable for asphalt or power floated floors</p>
COLOURS AVAILABLE	Clear, Red, Lt Grey, and Green
SUPPLIER	Paintmaster
COVERAGE	Approximately 6-8 sq metres per litre.
APPLICATION	Brush, roller or spray.
DRYING TIME	Under normal circumstances it should be touch dry in 6-8 hrs completely dry in 24hrs if well ventilated and conditions are dry.
STORAGE	Store away from naked flames. Secure lid on firmly between uses to prevent paint from skinning.
SURFACE PREP	Apply to clean dry surfaces. Ensure any oil or grease is removed. If new concrete allow to mature for several months before sealing.
THINNERS	White Spirit can be used for thinning.

AVAILABLE IN 20 LTS AND 205 LTR BARRELS

Safety Precautions

Refer to MSDS before use. Safety precautions must be strictly followed during storage, handling and use.
must be strictly followed during storage, handling and use.