

Data Sheet

Paintmaster Polyurethane Varnish – Satin & Gloss

1. Identification of the substance/preparation and of the company/undertaking

PRODUCT NAME	Paintmaster Polyurethane Varnish Satin & Gloss
PRODUCT INFO	Polyurethane solvent based resin. High quality, tough and durable varnish for interior use on bare or previously treated varnished timber. Suitable for use on doors, windows, furniture and all interior smooth planed timber.
COLOURS AVAILABLE	Clear only.
SUPPLIER	Paintmaster.
COVERAGE	Approximately 6-8 sq metres per litre.
APPLICATION	Brush or Roller.
DRYING TIME	Under normal circumstances it should be touch dry in 6-8 hrs if well ventilated and conditions are dry.
STORAGE	Store away from naked flames. Secure lid on firmly to prevent spillage.
SURFACE PREP	Apply to clean dry surfaces free from oil and grease.
THINNERS	White Spirit can be used for thinning.

AVAILABLE IN 20 LTS AND 205 LTR BARRELS

Safety Precautions

Refer to MSDS before use. Safety precautions must be strictly followed during storage, handling and use.