

Data Sheet

Paintmaster Q/D Alkyd Floor Sealer

1. Identification of the substance/preparation and of the company/undertaking

PRODUCT NAME	Paintmaster Quick Dry Alkyd Floor Sealer
PRODUCT INFO	A quick drying, low odour floor sealer for use on concrete and finished wood prior to topcoat. Recommended specifically for places that need low odour products such as food preparation areas. Also suitable for power floated floors.
COLOURS AVAILABLE	Clear
SUPPLIER	Paintmaster
COVERAGE	Approximately 6-8 sq metres per litre.
APPLICATION	Brush, roller or spray.
DRYING TIME	Under normal circumstances it should be dry in 6-8 hrs if well ventilated and conditions are dry.
STORAGE	Store away from naked flames. Secure lid on firmly between uses to prevent paint from skinning.
SURFACE PREP	Apply to clean dry surfaces. Ensure any oil or grease is removed. Do not use if surface temperature is below freezing.
THINNERS	Water can be used for thinning.

AVAILABLE IN 20 LTS AND 205 LTR BARRELS

Safety Precautions

Refer to MSDS before use. Safety precautions must be strictly followed during storage, handling and use.