

For MSDS & Technical Assistance ~ Email: [Sales@paintmaster.co.uk](mailto:Sales@paintmaster.co.uk)

## Data Sheet

### Paintmaster Scaffold & Pallet ID Paint

#### 1. Identification of the substance/preparation and of the company/undertaking

<b>PRODUCT NAME</b>	Paintmaster Scaffold & Pallet ID Paint
<b>PRODUCT INFO</b>	Hard wearing, high shine, oil based enamel gloss for Scaffold & Pallet Identification.
<b>COLOURS AVAILABLE</b>	All Colours available. British Standard Colours or RAL Colours.
<b>SUPPLIER</b>	Paintmaster
<b>COVERAGE</b>	Approximately 8 square metres per litre.
<b>APPLICATION</b>	Brush, Roller, Spray
<b>DRYING TIME</b>	Under normal circumstances it should be touch dry in 6-8hrs if well ventilated and conditions are dry.
<b>STORAGE</b>	Store away from naked flames. Secure lid on firmly between uses to prevent paint from skinning.
<b>SURFACE PREP</b>	Apply to a clean dry surface. Ensure any rust or damp is removed prior to application.
<b>THINNERS</b>	White Spirit can be used for thinning.

**AVAILABLE IN 20 LTS AND 205 LTR BARRELS**

#### **Safety Precautions**

Refer to MSDS before use. Safety precautions must be strictly followed during storage, handling and use.