

Head Office

Units 12-17 Bingswood Industrial Estate, Whaley
Bridge, High Peak, Derbyshire, SK237LY
Telephone: 0044 1663 733633
Fax: 0044 1663 735366
Website: www.paintmaster.co.uk
Email: Sales@paintmaster.co.uk



Data Sheet

Paintmaster Vinyl Matt, Soft Sheen & Silk Emulsion

1. Identification of the substance/preparation and of the company/undertaking

PRODUCT NAME	Paintmaster Vinyl Matt/ Soft Sheen/ Silk Emulsion
PRODUCT INFO	A water based, air drying, vinyl finish emulsion for interior use.
COLOURS AVAILABLE	White & Magnolia as well as British Standard Colours or RAL Colours.
SUPPLIER	Paintmaster
COVERAGE	Approximately 10-12 sq metres per litre.
APPLICATION	Brush, roller or spray.
DRYING TIME	Under normal circumstances the product should be touch dry within 2-4hrs if well ventilated and conditions are dry. Re-coat possible after 24hrs. Please note that drying times can differ in cold and damp conditions. The product may have a slight odour until dry. Applying the product in thin coats will allow a faster drying time and better finish.
STORAGE	Protect from frost and secure lid on firmly to prevent paint from drying out.
SURFACE PREP	Apply to clean dry surfaces.
THINNERS	Can be let down with water

AVAILABLE IN 20 LTS AND 205 LTR BARRELS

Safety Precautions

Refer to MSDS before use. Safety precautions must be strictly followed during storage, handling and use.